

OnSite PRO Inc.  
**FLOODSTOP**<sup>TM</sup>  
**Stop Flood Damage Before It Really Starts!**

FloodStop FS3/4H-90 is a point of use, leak detection and automatic water shut-off system designed for residential and commercial dwellings. The FS3/4H-90 uses two Motorized Ball Valves to automatically shut off the water supply whenever your washing machine leaks!

OnSite PRO Inc.  
28896 Mountain View  
Trabuco Canyon, CA 92679

(949) 589-7762  
(949) 589-7792 Fax  
www.onsiteproducts.com



### Install in Minutes!

Kit includes everything you need to protect your property:

3/4" Motorized Ball Valves installed on both hot and cold water inlets.

Water sensor is placed on the floor.

Control Unit is mounted with screws or Velcro (included).

Optional Power Sources: AC or Batteries, or Both!

### Technical Specifications:

UL listed class 2 wall adaptor, 115AC/9VDC

Signal Outputs: 2 Normally Closed

Motorized Ball Valves (2): CNC machined with 90 degree downward outlet.

Motors operate at 6VDC.

Rated 0-180 PSI. Max 250 PSI. Solid brass.

Rated 32-212 degrees F

Sensor: 1.25 X 7.5 inch, double sided. Additional sensors may be added in series.

Alarm: Beeping with Mute button.

### Washing Machines FS3/4H-90 3/4" Hose Fittings



### Other FloodStop Products:

FS3/4H-90 Washing Machine (Hose Fittings)

FS3/4NPT Water Heater 3/4" (MIP X FIP)

FS125NPT Water Heater 1.25" (MIP X FIP)

FS3/8C Dishwasher, Toilet (3/8" Compression)

FS1/4C Ice Maker (1/4" Compression)